### **20M**SERIES



E23M3

Technical data sheet for

## E23M3 ON THE SK23 STAND

Half Size Manual / Electric Convection Oven on a Stainless Steel Stand





### F23M3

Unit shall be a Moffat electrically heated Turbofan convection oven. The oven shall have a one piece vitreous enamel oven chamber, stainless top and sides and safe touch vented easy clean drop down door. Oven shall have capacity for three half size sheet pans. The oven shall have 2.8kW heating elements. The oven shall have a bi-directional single reversing fan system. The oven shall be controlled by a mechanical thermostat with a range of  $50\text{-}260^{\circ}\text{C}$ , a 60 minute bake timer, and feature a single halogen oven lamp. Oven shall be able to be bench mounted on 76mm feet or mounted on oven stand model SK23. Oven shall be fitted with a 15A plug-in cordset. Unit shall be supplied in 100% recyclable shipping packaging.

### SK23

Unit shall be a Moffat Turbofan stainless steel oven stand. The stand shall be constructed from stainless steel tube with castors, with front castors having dual swivel and wheel locks. It shall be fitted with 6 tray runners suitable for half size sheet pans. The stand shall be fully compatible with, and support, Turbofan Convection Oven models E22M2 and E23M3. Unit shall be supplied in 100% recyclable shipping packaging.

### STANDARD FEATURES

- 3 460mm x 330mm / 18" x 13" half size sheet pan capacity
- 3 GN 2/3 pan capacity
- 85mm tray spacing
- Compact 610mm width
- Bi-directional reversing fan system
- 2.8kW heating power
- 15A plug-in cordset fitted
- Vitreous enamel oven chamber
- Plug-in continuous oven door seal
- Safe-Touch vented drop down door
- Stay-Cool door handle
- Heavy-duty door hinges
- Easy clean door glass system
- Mechanical thermostat 50-260°C
- 60 minute timer with time up alarm
- Halogen oven lamp
- Dia. 180mm full stainless steel oven fan
- Anti-skid 50mm dia. 76mm high adjustable stainless steel feet
- 3 oven wire racks supplied
- 100% recyclable packaging

### ACCESSORIES

• Turbofan SK23 Oven Stand



## **20M**SERIES

# turbofan

E23M3

### E23M3 Half Size Manual / Electric Convection Oven on a Stainless Steel Stand

CONSTRUCTION

Vitreous enameled fully welded oven chamber Stainless steel front, sides and top exterior Stainless steel oven fan baffle and oven vent Removable 3 position chrome plated wire side racks Oven racks chrome plated wire (3 supplied) Stainless steel frame drop down hinged door 5mm thick door outer glass

5mm thick low energy loss door inner glass Heavy-duty counterbalanced door hinges Wear resistant powder coated welded door handle

Stainless steel control panel

Aluminised coated steel base and rear panels

CONTROLS

Power ON control panel indicator Mechanical thermostat 50-260°C Heating ON control panel indicator Manual 60 minute timer Time-Up control panel indicator and buzzer

Over-temperature safety cut-out

**CLEANING** 

Stainless steel top and sides continuous exterior panel Vitreous enameled oven chamber

Fully removable chrome plated oven side racks Removable stainless steel oven fan baffle

Full stainless steel oven fan

Easy clean door system with hinge out door inner glass

(no tools required) Removable plug-in oven door seal (no tools required)

76mm high stainless steel feet for easy access underside

**SPECIFICATIONS** 

Electrical Requirements

230-240V, 50Hz, 1P+N+E, 3kW, 12A

15A cordset fitted External Dimensions 610mm

Height 607mm including 76mm feet

Depth 642mm Oven Internal Dimensions 495mm Width Height 305mm 340mm Depth Volume 0.51m3

Oven Rack Dimensions Width 460mm Depth 330mm

Nett Weight (E23M3)

42.4kg

Packing Data (E23M3)

54.6kg 0.34m3

750mm Width 705mm Height 635mm Depth

### SK23 Stainless Steel Stand

All stainless steel welded frame oven stand for

Turbofan E22 and E23 Series ovens

6 position tray runners standard

4 76mm diameter wheel swivel castors standard with

2 front castors with dual swivel and wheel lock

Welded 38mm and 32mm square tube front and rear frames

Welded rack supports/side frames

Top frame oven supports suit Turbofan E22 and E23 Series oven mounting

Supplied CKD for assembly on site

External Dimensions (SK23 Oven Stand)

Width 610mm 880mm Height 530mm Depth

Nett Weight (SK23 Oven Stand)

16kg

Packing Data (SK23 Oven Stand)

18kg

0.09m3

630mm Width Height 900mm Depth 152mm

### INSTALLATION CLEARANCES

Rear 25mm LH Side 25mm RH Side 25mm

CLEARANCE FROM SOURCES OF HEAT

A minimum distance of 300mm from the appliance sides is

## MOFFAT

Australia www.moffat.com.au New Zealand www.moffat.co.nz www.turbofanoven.com

### Australia Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au

New South Wales Telephone 02-8833 4111 nswsales@moffat.com.au

South Australia Telephone 03-9518 3888 vsales@moffat.com.au

Queensland Telephone 07-3630 8600 qldsales@moffat.com.au

Western Australia Telephone 08-9202 6820 bgarcia@moffat.com.au

### New Zealand Moffat Limited

Christchurch 45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

Auckland Telephone 09-574 3150 sales@moffat.co.nz





ISO9001 Quality Management Standard

Designed and manufactured by **MOFFRT** 

IS09001

All Turbofan products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products. Moffat Limited reserves the right to change specifications and design without notice



© Copyright Moffat Ltd AN.TFN.S.1501

